

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ :

F04B 53/16 // 53/14, F16J 10/02

A1

(11) International Publication Number:

WO 00/65235

(43) International Publication Date:

2 November 2000 (02.11.00)

(21) International Application Number: PCT/DK99/00227

(22) International Filing Date: 22 April 1999 (22.04.99)

(71) Applicant (for all designated States except US): NVB INTERNATIONAL [DK/DK]; Gaerdet 12, P.O. Box 69, DK-3460 Birkerød (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VAN DER BLOM, Nicolaas [NL/DK]; Gaerdet 12, DK-3460 Birkerød (DK).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: A DEVICE COMPRISING A COMBINATION OF A CHAMBER AND A PISTON

(57) Abstract

The object of the invention is to provide a reliable and inexpensive combination of a chamber and a piston to be used in any device where such a combination is needed so that it complies with specific demands towards the operation force for e.g. pumps, specifically manually operated pumps. By a device comprising a chamber and a piston positioned inside the chamber said chamber and said piston relatively movable to each other in a predetermined direction of movement between a first position and a second position of which the cross-section of the chamber in a plane perpendicular to the direction of movement is larger at the first position than at the second position, the change in the cross section of the chamber is essentially continuous between the first position and the second position and the cross-section of the piston in a plane perpendicular to the direction of movement is arranged to adapt itself to the cross-section of the chamber. It is further possible that the piston has a fixed geometrical shape, that the wall of the chamber has different sizes of cross-sections in the direction of the movement and is arranged to adapt itself to the piston. Moreover, both the piston and the wall of the chamber can adapt itself to each other.

